

## 38895 YALTE D 09 8W WW-B

Facade luminaire

5905339388957



Kanlux YALTE is a modern series of linear facade luminaires with a minimalistic design and a wide range of applications, suitable for use in interiors as wall arrangements, mirrors, or painting illumination. Made of an aluminum body and a polycarbonate lampshade. The 330° adjustment allows for precise setting of the lighting angle. Available in two color temperatures 3000K and 4000K, and in single or double mounting variants. The IP54 rating provides protection against water and dust, while the 5-year warranty ensures long-term and trouble-free use.

### GENERAL DATA:

**Colour:** black

**Place of assembly:** wall mounted

**Place of application:** Indoors and outdoors

**Minimum distance from the illuminated object:** 0,5m

**Compatible with a dimmer:** no

**RAL:** 9005

**Wykrywanie ruchu:** no

**Length [mm]:** 80

**Width [mm]:** 45

**Height [mm]:** 900

**Mercury content in the lamp [mg]:** 0

**Integrated LED light source:** yes

**Number of modules (LED light source):** 1

### TECHNICAL DATA:

**Rated voltage [V]:** 220-240 AC

**Rated frequency [Hz]:** 50

**Maximum power [W]:** 8

**Class of protection against electric shock:** I

**Lampshade material:** PC

**Enclosure material:** aluminum alloy

**Diode type:** LED SMD

**Luminous flux [lm]:** 340

**Useful luminous flux of the light source  $\Phi_{use}$  [lm]:** 950


**Useful luminous flux of the light source  $\Phi_{use}$  [lm]:** in sphere (360°)

**Colour temperature:** Warm white

**Correlated colour temperature [K]:** 3000

## 38895 YALTE D 09 8W WW-B

### Facade luminaire



**Colour consistency in McAdam ellipses :** 6

**Colour rendering index:** 80

**Cap (Light source) :** solder pads

**Service life [h] :** 30000

**Number of on/off cycles :**  $\geq 40000$

**Luminous efficiency of the lamp [lm/W] :** 43

**Ambient temperature range to which the product can be exposed :**  $-15 \div 35$

**Connection type:** Bolt terminal block

**Range of sections of wires used [mm<sup>2</sup>] :**  $0,75 \div 1,5$

**Lighting-fixture angle regulation [°] :** 330

**IP class:** 54

#### LOGISTIC DATA:

**Unit of measurement:** unit

**Packaging method:** 8

**Number of units in the secondary packaging :** 1

**Number of units in the packaging :** 8

**Net unit weight [g] :** 852

**Grammage [g] :** 1066.25

**Gross unit weight [g] :** 1004

**Length of a unit pack [cm] :** 8.5

**Width of a unit pack [cm] :** 5

**Height of a unit pack [cm] :** 91

**Weight of a cardboard box [kg] :** 8.53

**Width of a cardboard box [cm] :** 22.5

**Height of a cardboard box [cm] :** 19.5

**Length of a cardboard box [cm] :** 92

**Volume of a cardboard box [m<sup>3</sup>] :** 0.040365

#### ADDITIONAL INFORMATION:

- 5 years Warranty under the terms of the warranty statement, available on our website

