

PRODUCT DATASHEET Smart+ Wifi Outdoor Flex IP44 5M RGB TW

SMART+ WIFI OUTDOOR FLEX | Decorative LED Strips for outdoor use with WiFi technology



Areas of application

- Outdoor applications
- Indirect lighting

Product benefits

- Easy and quick installation
- Uses multi color and cold or warm white light for most flexible lighting scenes

Product features

- Dimmable
- RGB color control, approx. 16 million color options adjustable
- Adjustable color temperature via Tunable White: 2,700...6,500 K
- Flexible, bendable LED strips
- Type of protection: IP44
- Controllable via SMART+ App (with minimum Android 8.0 or iOS 14.0)



TECHNICAL DATA

Electrical data

| Nominal wattage | 14.50 W | |
|---------------------------|-----------|--|
| Nominal voltage | 220240 V | |
| Mains frequency | 5060 Hz | |
| Nominal current | 85.000 mA | |
| Inrush current | 28 mA | |
| Power factor λ | > 0.5 | |
| Total harmonic distortion | < 20 % | |
| Protection class | Ш | |

Photometrical data

| Luminous flux | 960 lm | |
|--|------------------------------------|--|
| Total luminous flux of contained light sources | 1600 lm | |
| Luminous efficacy | 66 lm/W | |
| Color temperature | 27006500 K | |
| Light color (designation) | Red / Green / Blue / Tunable White | |
| Color rendering index Ra | ≥80 | |
| Standard deviation of color matching | < 6 sdcm | |
| Flickering metric (Pst LM) | <1 | |
| Stroboscope effect metric (SVM) | < 0.4 | |
| Photobiological safety group acc. to EN62778 | RG1 | |
| Beam angle | 120 ° | |

Dimensions & Weight

| Length | 5000.00 mm |
|----------------|------------|
| Width | 11.50 mm |
| Height | 4.50 mm |
| Product weight | 510.00 g |

SMART WIFI OUTD FLEX 5M RGB TW

Materials & Colors

TW

| Product color | White |
|-----------------|----------|
| Housing color | White |
| Body material | Silicone |
| Cover material | Silicone |
| Mercury content | 0.0 mg |

Application & Mounting

| Ambient temperature range | -20+40 °C | |
|------------------------------|------------------|--|
| Temperature range at storage | -2080 °C | |
| Type of connection | Plug type C (EU) | |
| Type of protection | IP44 | |
| Dimmable | Yes | |
| Type of dimming | WiFi | |
| Mounting type | Surface | |
| Application environment | Outdoor | |

Lifespan

| Lifespan L70/B50 at 25 °C | 30000 h |
|----------------------------|---------|
| Number of switching cycles | 15000 |

Certificates & Standards

| Standards | CE |
|----------------------------------|-----------------|
| Replaceable light source (EPREL) | Not replaceable |

Additional product data

| Product remark Reset settings to default by switching the product on for three second and off for three seconds and repeating this five times. | onds |
|---|------|
|---|------|

EQUIPMENT / ACCESSORIES

- Control via app or voice control requires compatible Smart home system
- Complete mounting and connecting accessories included
- For control via SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)

Safety advice

- To reduce the risk of strangulation the flexible wiring connected to this luminaire shall be effectively fixed to the wall if the wiring is within arm's reach.
- Do not connect the rope light to the supply while it is wound onto a reel. Do not use the lightstrip when covered or recessed into a surface. The string of lights may not be operated within the packaging. Do not open the lightstrip.

- Check wall-ceiling for suitability. If uncertain, seek professional advice.

DOWNLOAD DATA

| | Documents and certificates | Document name | |
|-----|--|-------------------------------------|--|
| POF | User instruction / safety instructions | UI SMART WIFI OUTDOOR FLEX | |
| POF | Legal information | Legal Insert SMART WIFI OUTD FLEX | |
| POF | Declarations of conformity | SMART WIFI OUTD FLEX 5M RGB TW IP44 | |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4099854095184 | Folding box 1 | 70 mm x 210 mm x 200 mm | 655.00 g | 2.94 dm ³ |
| 4099854095191 | Shipping box 4 | 420 mm x 235 mm x 165 mm | 3006.00 g | 16.29 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- Further information and frequently asked questions (FAQs) at www.ledvance.com/consumer/smart/faq

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

Page 4 of 4